

COLD WATER

Tucson

T.S. Total Stop

Models: 1211 LP/1509 LP

T.S. Total Stop 24V

Models: 1713 LP/2017 LP



CRANKSHAFT



1450
RPM



WATER
COOLING

Models: 1713 LP/2017 LP



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection (mod. 1 ph)
- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (mod. 3 ph)
- Three ceramic coated pistons (Tucson 1211/1509/2017). Three full ceramic pistons (Tucson 1713)
- Suction and delivery S. S. valves.
- Low voltage and delayed Total Stop (mod. 3 ph)
- Detergent built-in tank for indirect suction (2,8 lt.).
- Pressure regulator.
- Glycerine pressure gauge.

	Tucson 1211 LP	Tucson 1509 LP	Tucson 1713 LP	Tucson 2017 LP
code	8.671.0001	8.671.0002	8.671.0003	8.671.0004
operat. pressure/max	120/150 bar-1740/2175 psi	150/160 bar-2175/2320 psi	170 bar-2465 psi	200 bar-2900 psi
delivery rate	660 l/h-2.91 GPM	540 l/h-2.37 GPM	780 l/h-3.43 GPM	1000 l/h-4.4 GPM
abs. power/voltage	3000W - 230V~50Hz 1 ph	3000W - 230V~50Hz 1 ph	5200W - 400V~50Hz 3 ph	7500W - 400V~50Hz 3 ph
motor/pump type/RPM	MP3/1450 RPM	MP3/1450 RPM	MPW3.5/1450 RPM	MPW3.5/1450 RPM
max. water inlet temperature	40 °C	40 °C	40 °C	40 °C
dimension/weight	76x41x75cm/33 kg - 72,6 lbs	76x41x75cm/33 kg - 72,6 lbs	76x40x75cm/42 kg - 92,4 lbs	76x40x75cm/44 kg - 96,8 lbs

STANDARD EQUIPMENT

- 3.700.0036 Gun M22 - 3/8 (mod. 1211 LP/1509 LP).



- 3.700.0030 Gun M22 - 3/8 with rotating coupling (mod. 1713 LP/2017 LP).



- 3.701.0027 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0047 Nozzle type 030 (mod. 1509 LP)
- 3.103.0052 Nozzle type 055 (mod. 1713 LP/2017 LP)



- 4.618.0143 High pressure hose 10 m (mod. 1713 LP/2017 LP)
- 4.618.0049 High pressure hose 8 m (mod. 1211 LP/1509 LP)



- Power cable 5 m